



CERTIFICATE NO: CM70065
Date of issue: 6 October 2020

PRODUCT CERTIFICATE

Loxo Cladding System



BUREAU
VERITAS

KEY INFORMATION

1 CERTIFICATE HOLDER DETAILS

Loxo Cladding Systems NZ Ltd
PO Box 10-176,
Christchurch
New Zealand

E: info@loxocladding.co.nz
Ph: +64 3 372 3343
www.loxocladding.co.nz



2 PRODUCT CERTIFICATION BODY

Bureau Veritas Australia Pty Ltd
3/435 Williamstown Road
Port Melbourne VIC 3207
Australia

Ph: 1800 855 190
www.bureauveritas.com.au

Bureau Veritas Australia Pty Ltd

The complaints process for this certificate
can be found here:
www.bureauveritas.com.au/your-feedback

3 SUMMARY OF DESCRIPTION OF BUILDING METHOD OR PRODUCT

The Loxo Cladding System consists of 50mm or 75mm-thick steel-reinforced Autoclaved Aerated Concrete (AAC) panels, 2200mm wide x 600mm high, mounted horizontally on H3.2 treated timber or high density expanded polystyrene (EPS) cavity battens and screw fixed to the external load-bearing wall. The Loxo Cladding System includes a plastered rendered coating to the exterior face of the panel.

*Continuation of description can be found in item 9. Supporting Information about Description of Building Product or Method.
Matters that should be taken into account in the use or application of the building method or product can be found in item 6. Conditions and Limitations of Use.*

4 SUMMARY OF INTENDED USE OF BUILDING METHOD OR PRODUCT

The Loxo Cladding System is a non-load-bearing external wall cladding fixed to battens on an external load-bearing wall.

Continuation of intended use can be found in item 8. Supporting Information about Intended use of Building Product or Method.

5 BUILDING CODE PROVISIONS

The performance clauses of the New Zealand Building Code that are relevant to the intended use and with which the building method or product complies or contributes to (where used as part of a system).

B1 Structure: B1.3.1, B1.3.2, B1.3.3(a, f, h, j, q), B1.3.4
B2 Durability: B2.3.1(a), B2.3.1(b), B2.3.2
C3 Fire affecting areas beyond the fire source: C3.6 (contributes to), C3.7
E2 External moisture: E2.3.2, E2.3.5, E2.3.7
F2 Hazardous building materials: F2.3.1

How the building method or product complies or contributes can be found in item 12. Basis for Certification. Any qualifications on the extent of that compliance can be found in item 6. Conditions and limitations of use.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product that is the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.

This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.
CERTIFICATE V1.3



PRODUCT CERTIFICATE

Loxo Cladding System



6 CONDITIONS AND LIMITATIONS OF USE

- The Loxo Cladding System shall only be used on buildings that are:
 - timber-framed to NZS3604:2011 Timber framed buildings or steel-framed to NASH Standard Part 2: May 2019 Light Steel Framed Buildings, and
 - within the scope of Acceptable Solution E2/AS1 para 1.1, and with risk score not greater than 20, and
 - located in a wind zone up to and including Very High wind zone (as specified in NZS3604:2011), and
 - located in any seismic zone (as specified in NZS3604:2011), and
 - in any exposure zone (excluding microclimates) (as specified in NZS3604), and
 - in risk groups SH, SM, or VP (as defined in Acceptable Solution C/AS1 and Acceptable Solution C/AS2) without sprinklers, located any distance from a relevant boundary with the proviso that Loxo (VH) EPS Battens must not be used for the Loxo Boundary Fire Wall System located closer than 1m from a relevant boundary.
- The Loxo Cladding System shall be installed:
 - on walls that are vertical, and
 - in accordance with the Loxo Cladding Systems Technical Manual, August 2020, by a tradesperson with an LBP (Carpentry) license approved by Loxo; the reinforced render and coating system shall be applied by an applicator with an LBP (External Plastering) license approved by Loxo; and any components and accessories supplied by Loxo Cladding Systems NZ Ltd shall be carried out by licensed LBP contractors, approved by Loxo Cladding Systems NZ Ltd. Please contact Loxo Cladding NZ Ltd for details of licensed Loxo applicators.
- Where the Loxo Cladding System is used as a boundary fire wall it shall be designed and installed in accordance with the Loxo Cladding Systems Boundary Fire Walls Technical Manual, June 2018.
- All joinery used in conjunction with the Loxo Cladding System shall meet the requirements of NZS 4211:2008 Specification for performance of windows and be installed with vertical jambs and horizontal heads and sills.

NOTE: Together, items 3, 4, 5 and 6 define scope of use.

7 HEALTH AND SAFETY INFORMATION

The compliance with any manufacturer's installation instructions, maintenance, OH & S statements, MSDS's and other Health and Safety declarations will provide the necessary Health and Safety Information pertaining to the product. Refer to section 12 for specific detail of compliance with the performance requirements of clauses F1 to F9 of the Building code.

8 SIGNATURES

Sam Guindi
Product Certification Manager

For and on behalf of
Bureau Veritas Australia Pty Ltd

Marcus Stufkens
Director

For and on behalf of
Loxo Cladding Systems NZ Ltd



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product that is the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.

This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.
CERTIFICATE V1.3

PRODUCT CERTIFICATE

Loxo Cladding System

SCHEDULE: INFORMATION THAT SUPPORTS KEY INFORMATION

9 SUPPORTING INFORMATION ABOUT DESCRIPTION

The Loxo Cladding System has the following components:

Autoclaved Aerated Concrete (AAC) panels 2200mm wide x 600mm high, 50mm or 75mm thick

Battens:

- Classic (VH) EPS (22mm) battens: 22mm x 40mm x 1200mm
- Deluxe (VH) EPS (50mm) battens: 50mm x 40mm x 1200mm
- H3.2 treated timber battens

Basecoat Plasters:

- Grano Adhesive Mortar with GranoMesh render or Masons Base Coat with Masons Meshing Render

Finishing Plasters and Coating:

- Granosite High Build Acrylic Texture Finish
- Granosite Cement Based Texture - Sponge Finish
- Masons Cement Based Texture - Sponge Finish
(as specified in the Loxo AAC Panel Specification August 2020 and related product specifications Granosite Grano Sponge Finish Satin, Granosite GranoAntique Trowel Satin, Granosite GranoMarble Trowel Satin, Masons Enviro 1mm Sponge Render)

Fixings:

- Bugle head self-cutting screws (Grade 3 or 4) 14-10 x 100mm long
- Bugle head self-cutting screws (Grade 3 or 4) 14-10 x 150mm long

Panel Adhesive:

- Loxo Panel Adhesive is a polymer modified cement-based adhesive mortar
- Bostik FixAll Tile Adhesive

Corrosion Protection Paint:

- Loxo Primer
- CRC ZINC IT

Flashings:

- Loxo PVC jamb flashing
- Loxo PVC sill flashing
- Metal flashings (supplied and installed by others)

Mouldings

- Loxo PVC slotted vermin control cavity closer Classic (22mm)



PRODUCT CERTIFICATE

Loxo Cladding System



- Loxo PVC slotted vermin control cavity closer Deluxe (50mm)
- Loxo PVC control joint moulding
- Loxo PVC base shoe moulding 50mm

10 SUPPORTING INFORMATION ABOUT INTENDED USE

Further details regarding the use of the product can be found in the following documentation:

1. Loxo Cladding Systems Panel Systems Technical Manual, Aug 2020
2. Loxo Cladding Systems Boundary Fire Walls Technical Manual, June 2018
3. Masons Enviro 1 mm Sponge Render, July 2020
4. Granosite Paintworks Specification - Grano Sponge Finish Satin Version 1, August 2013
5. Granosite Paintworks Specification - GranoAntique Trowel Satin Version 1, August 2013
6. Granosite Paintworks Specification - GranoMarble Trowel Satin Version 1, August 2013
7. Loxo AAC Panel Specification, August 2020

11 SUPPORTING INFORMATION ABOUT CONDITIONS AND LIMITATIONS OF USE

NA



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product that is the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.

This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.
CERTIFICATE V1.3

12 BASIS FOR CERTIFICATION

B1 Structure - By analysis and comparison with Verification Method B1/VM1

B2 Durability - By analysis and comparison with Verification Method B2/VM1 and Acceptable Solution B2/AS1

C3 Fire affecting areas beyond the fire source - By testing and comparison with Verification Method C/VM2 and Acceptable Solutions C/AS1 and C/AS2

E2 External moisture - By testing and comparison with Verification Method E2/VM1 and Acceptable Solution E2/AS3

F2 Hazardous building materials - By comparison with Building Code performance requirement F2.3.1

13 SUPPORTING DOCUMENTATION FOR CERTIFICATION

1. Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B1 Structure, 1st Edition (Amendment 19), 28 November 2019
2. Acceptable Solutions and Verification Methods for New Zealand Building Code Clause B2 Durability, 2nd Edition (Amendment 12), 28 November 2019
3. C/VM1 and C/AS1 Acceptable Solution and Verification Method For New Zealand Building Code Clauses C1-C6 Protection from Fire, (Amendment 3), 1 July 2014
4. C/AS2 Acceptable Solution for Buildings other than Risk Group SH for New Zealand Building Code Clauses C1-C6 Protection from Fire, 1st Edition (Amendment 1), 22 October 2019
5. Verification Methods and Acceptable Solutions for New Zealand Building Code Clause E2 External Moisture, 3rd Edition (Amendment 9), 27 June 2019
6. TM Consultants LOXO Wall Cladding Assessment, 19 March 2020
7. Exova Warringtonfire Assessment Report No: 38259000.4_AS1530.4-2014_Horizontal_50mm
8. CSIRO Certificate of Test No. 2363A 172-mm thick Load-bearing Loxo Autoclaved Lightweight Aerated Concrete (AAC) panel wall system test to AS1530.4-2005, 27 April 2012
9. Identifibre Report No. 33238-1-bsa, 12 December 2018
10. Ian Bennie and Associates Test Report No.2015-102-S1 NASHI 50mm Wall System, January 2016
11. CCANZ CP01:2014 Code of Practice for Weathertight Concrete and Concrete Masonry Construction, 1 January 2014
12. Sharp and Howells Report Test Report No. 19-0125B Testing of Reinforced Autoclaved Aerated Concrete Members to AS5146.2, 17 October 2019
13. Loxo Cladding Systems Panel Systems Technical Manual, Aug 2020
14. Loxo Cladding Systems Boundary Fire Walls Technical Manual, June 2018
15. Masons Enviro 1 mm Sponge Render, July 2020
16. Granosite Paintworks Specification - Grano Sponge Finish Satin Version 1, August 2013
17. Granosite Paintworks Specification - GranoAntique Trowel Satin Version 1, August 2013
18. Granosite Paintworks Specification - GranoMarble Trowel Satin Version 1, August 2013
19. Loxo AAC Panel Specification, August 2020

14 CONDITIONS RELATING TO NOTIFICATION

- (a) the certificate holder notifies the product certification body (Bureau Veritas) in writing of any intended change to any of the following particulars:
- (i) the name, address, or contact details of the certificate holder;
 - (ii) any address of a location where a certified product is produced or manufactured;
- (b) the certificate holder notifies the product certification body in writing of any intended change, modification, or alteration to any of the following:
- (i) the certified building method or product;
 - (ii) the method of its production or manufacture;
 - (iii) the product quality plan prepared in respect of the certified building method or product;
 - (iv) the application or installation instructions for the certified building method or product;
 - (v) any documentation relating to the use and maintenance of the certified building method or product;
- (c) if the certificate holder has any reason to suspect that the certified building method or product does not comply with the Building Code, the certificate holder notifies the product certification body in writing of the reason for that suspicion:
- (d) if the certificate holder or the product certification body finds that a certified building method or product that has been released on the market does not comply with the Building Code, the certificate holder discloses that fact in disclosure statements published in a form that is acceptable to the product certification body and to the chief executive:
- (e) if the certificate is suspended or revoked, the certificate holder—
- (i) notifies all customers to whom the building method or product is regularly supplied; and
 - (ii) immediately ceases using the certificate, the mark of conformity, and any reference to the number of the certificate.