

Loxo Panel Adhesive

Bostik Fixall (Ref 30804123) is the authorised **Loxo Panel Adhesive** for all Loxo system applications. This is a polymer modified cement-based adhesive mortar supplied in 20kg bags. Loxo Panel Adhesive to be used to mortar all panel joins and bases on AAC panels.

For system and CodeMark compliance, Loxo Distributors / Agents / Applicators / Installers must ensure only authorized products are used and installed correctly as per system and manufacturer requirements.

Bags must be kept dry and have a shelf life of 12 months. For quality assurance purposes Fixall and Bostik additive products are supplied **by Loxo Cladding NZ or an Authorised Loxo Distributor.**



APPLICATION

Bostik Fixall is mixed on-site with clean water (see instructions printed on each bag) and is applied to all edges of the panels by trowel.

Use only in ambient conditions between 5 and 35° C. Do not use in windy or very humidity conditions.

To support a strong bond in hot dry climates, panel edges can be wet before application to reduce excessive absorption of moisture. Alternatively, Bostik NZ recommends application of Bostik **Ultra Multiprime A530** general purpose primer for porous surfaces.

MIXING - 20kg powder mixes into 5 – 5.5 litres of water, 1kg into 250 - 275 ml water

- add water to bucket
- mix powder into water with mechanical stirring
- mix until smooth
- allow to stand for 2 minutes and mix again before using

Important: The paste can “wet out” during mixing so make sure that it is mixed sufficiently before adding more liquid. Do not add more liquid after the initial mixing. Discard when the product stiffens in the bucket. Use a drill with suitable mixing paddle designed for the task and do not mix by hand. Refer separate downloads for Bostik SDS and TDS.

Other Loxo approved BOSTIK products.

Megalastic - General purpose additive for cement-based systems.



This is an optional additive that can be mixed in with water to upgrade Fixall flexibility and bond strength and increase working time.

Loxo Cladding NZ Ltd recommends using this additive for inter-tenancy firewalls in fast drying conditions to reduce the evaporation rate of water in the adhesive.

Add 1-part Megalastic to 3-parts water (25%), increase up to 1 to 1 (50%) if required. Use this solution instead of straight water when mixing with Fixall.



Tuff as Nails Original (Poly Safe) – Loxo approved **Construction Adhesive** for bonding flooring panels to floor structure, and for fixing cladding battens to building wrap. Not for use in firewall applications.



MS SafeSeal - - Sealing expansion joints

Bostik products are available from Loxo NZ or a Loxo Distributor. Refer to Bostik NZ website for current product information and safety data sheets. https://www.bostik.com/newzealand/en_NZ